


FLEXIBLE COUPLING

UL/FM


Rated ϕ (mm)	Outside ϕ (mm)	Rated Pressure MPa	Pipe max distance (mm)	Rotational angle (°)	Deflection (mm)	Bolts and nuts measurement	ϕ (mm)	L (mm)	H (mm)
25	33.7	2.5	2	3.6	62	2-M10 x 45	61	98	48
32	42.4			2.7	47		70	104	
40	48.3		2.5	2.4	42		76	112	
50	57.0			2.3	42	2-M10 x 55	86	124	
50	60.3			2.3	42		88	124	
65	76.1			1.9	33		102	140	
80	88.9			1.6	28		118	162	
100	108.0			1.7	29	2-M12 x 65	146	186	51
100	114.3			1.6	28		150	195	
125	133.0			1.4	24		170	220	
125	139.7			1.3	23		178	216	
150	159.0			1.2	20	2-M12 x 75	198	246	
150	165.1			1.1	19		205	246	
150	168.3			1.1	19	2-M16 x 85	210	266	
200	219.1	1.6	3.2	0.8	14	2-M16 x 100	264	330	60
250	273.0			0.7	12	2-M22 x 130	328	420	64
300	323.9			0.6	10		380	454	
350	377.0			0.5	8	3-M22 x 130	445	480	77

FEATURES:

Code: **GF-003**.

Flexible coupling made of ductile iron.

UL/FM approved.

Color: Red RAL3000.

