

MANCHON DE RÉPARATION

UNE-545



Ø DN	TAILLE	L (mm)	VIS
45-55	1,5"	150	M16 X 2
48-56		200	
45-55		300	
60-67	2"	150	M16 X 2
		191	
		200	
88-98	3"	300	M16 X 3
		150	
		191	
95-105	3"	200	M16 X 2
		300	
		150	
108-118	4"	191	M16 X 2
		200	
		330	

Ø DN	TAILLE	L (mm)	VIS
115-128	4"	150	M16 X 2
		191	
		2001	
130-145	5"	300	M16 X 3
		150	
		191	
140-155	5"	300	M16 X 3
		150	
		191	
158-172	6"	300	M16 X 3
		150	
		191	
168-182	6"	200	M16 X 2
		300	
		150	
180-193	7"	191	M16 X 2
		300	
		150	

Ø DN	TAILLE	L (mm)	VIS
180-193	7"	200	M16 X 2
		300	
		191	
190-203	7"	200	M16 X 2
		300	
		191	
217-229	8"	200	M16 X 2
		300	
		191	
225-240	8"	300	M16 X 3
		200	
		191	
243-260	10"	300	M16 X 3
		200	
		191	
270-280	11"	300	M16 X 3
		200	
		191	
313-336	12"	300	M16 X 3
		300	
		300	

CARACTÉRISTIQUES:

Fabriqu  en **Acier Inoxydable SS304** et **Fonte Ductile**.

Boulons et  crous en acier inoxydable; poign e en Acier inoxydable et fonte ductile.

Conforme   la **norme UNE-EN 545**.

EPDM joint en caoutchouc, conforme   la **norme UNE-EN 681-1**.

Rev tement de **peinture  poxy bleu**.

