

Equipped fire fighting hydrant - bms hinged

WINDER CONNECTION THROUGH HOSE

REFERENCE	MODEL	CABINET	DOOR
BMSBISRR	BMS-20 EP	Red	Red semi-blind
BMSBISRB	BMS-20 EP	Red	White semi-blind
BMSBICRR	BMS-20 EPF	Red	Blind red
BMSBISRX	BMS-20 EPI	Red	Steel semi-blind
BMSBICRX	BMS-20 EPFI	Red	Ciega inoxidable
BMSBISGG	BMS-20 EP	Gray	Stainless blind
BMSBICGG	BMS-20 EPF	Gray	Gray semi-blind
BMSBISGX	BMS-20 EPI	Gray	Steel semi-blind
BMSBICGX	BMS-20 EPFI	Gray	Stainless blind
BMSBISXX	BMS-20 EPI	Steel AISI-304	Steel semi-blind
BMSBICXX	BMS-20 EPFI	Steel AISI-304	Stainless blind
BMSBIRAX	BMS-20EP	Red	Steel glazing
BMSBIGAX	BMS-20EP	Gray	Steel glazing
BMSBIXAX	BMS-20EPF	Inoxidable AISI-304	Steel glazing
BMSBIDSA	BMS-20 SA	No cabinet	
BMSBIMEE		Built-painted trim frame.	
BMSBIMEX		INOX recessed trim frame.	



SPECIFICATIONS:

BIE of 25 mm. According with the **UNE - EN 671-1** norm and certified by AENOR and CE.

- **Vertical cabinet** made of polished sheet and painted with **epoxy-polyester**, red **RAL-3000**.
- Lockable door slip and security seal.
- Methacrylate included in semi-blind door models.
- Hinged **winder** axial feed.
- **Globe valve** 1" chrome-plated brass with drain and reduction **gear wheel**.
- **Pressure gauge** scale 0-16 Kg / cm².
- Triple effect lance (jet, spray and closing), King type of 25 mm. Hose connected to buttress threaded hole Ø10mm.
- 20mts. **rigid hose** of 25 mm. According to UNE 23091 / 3A (UNE-EN- 694) norm.
- **Supply hose** between the valve and the spool.
- Reversible **cabinet** with power input water on all sides.
- Equivalent **diameter** 10mm/factor K= 42.

HEIGHT	WIDTH	DEPTH
660	600	210